

CAMLUX MAX SERIES

The Dracast Camlux Series Max On-Came Light is enclosed in an anodized aluminum blue case. It features 280 LED's on the light board with a 45° flood beam angle.



Photometric Data		1.5 ft / 0.5 m	3 ft / 0.9 m	6 ft / 1.8 m	9 ft / 2.7 m
CAMLUX MAX - BICOLOR (SURFACE MOUNT LED)	3200K	4920 lux	1580 lux	452 lux	216 lux
	4400K	10062 lux	3480 lux	965 lux	450 lux
	5600K	5280 lux	1950 lux	540 lux	262 lux
CAMLUX MAX - DAYLIGHT (SURFACE MOUNT LED)	5600K	9998 lux	3529 lux	933 lux	427 lux

Part No.	Items Included
DRCAMLMAXB	<ul style="list-style-type: none"> •Nylon Soft Carrying Case •D-Tap Cable •Hot Shoe Mount •Diffusion Filter
DRCAMLMAXD	<ul style="list-style-type: none"> •Nylon Soft Carrying Case •D-Tap Cable •Hot Shoe Mount •Diffusion Filter

Specifications | Details

Optical System	280 Surface LED
Light Aperture	6.75" x 4.25"
Beam Angle	45°
Weight	2.5 lbs (1.13 kg)
Handling	Hot Shoe Base
Mounting	1/4"-20 Threaded Hole
Swivel Angle	120 Degrees
Voltage Input	7.2 - 8.4 VDC
Power Consumption	18 W
AC Connection	Standard Barrel Connection
Battery Connection	Dual NPF
Battery DC Voltage	12 V
Color Temperature	3200K - 5600K, 5600K
Color Rendition	CRI > 95
Dimming	10 - 100% Continuous
Controls	Local On-Board Manual Controls
Housing Build	Anodized Aluminum Housing
Est. LED Lifetime	50,000 Hours



Available Accessories

DRBK2NPF6600	NPF- TWO BATTERY / CHARGER COMBO 6600 mAh
DRBA6600NPF	NPF-BATTERY 6600 mAh
DRPSONCAM	ON-CAMERA POWER SUPPLY
DRLSCLS	COMPACT LIGHT STAND

